



Glasroc F MULTIBOARD

Five high performances
in one board



Glasroc F MULTIBOARD is non-combustible and depending on which of the three thickness you use can give you up to 120 minutes fire resistance. Great for anywhere presenting a fire risk including:

- Fire-rated partitions
- Timber ceiling joists
- Kitchens
- Boiler cupboards
- Garages



These days, curves are big business, adding interest and extra value to many kinds of domestic, shop and bar fitting projects. With 6mm Glasroc F MULTIBOARD you can quickly and easily create stylish curves without pre-wetting. Perfect for:

- Archways
- Curved reveals
- Barrel vaults and partitions using Gypframe CurveLyner Channel and curved **CasoLine MF** ceiling systems.



Glasroc F MULTIBOARD will stay looking crisp and new in situations where other boards may start to look shabby. It resists cracking, shattering, and denting in vulnerable or high traffic areas, so use it with confidence in:

- Play rooms
- Hallways
- Corridors
- Stairwells
- Utility areas



Poor damp resistance is a major cause of costly call-backs. Glasroc F MULTIBOARD will protect your profits, working perfectly indoors or outside in semi-exposed areas. Ideal for:

- Ceramic tile backing
- Panelling in kitchens
- Bathrooms
- Rooms adjacent to shower cubicles
- Soffits
- Carport linings



The smooth and durable surface of Glasroc F MULTIBOARD is so good you may want to forget decorating. Or alternatively, if you prefer, it can be jointed and then either painted or papered. It also takes a plaster skim directly without preparation using Thistle BoardFinish, Thistle MultiFinish or Thistle Magnetic Plaster.



Thickness mm	Width mm	Length mm
6	1200	2400 3000
10	1200	2400 2700 3000
12.5	1200	2400 2700 3000

Glasroc F MULTIBOARD

It's beautifully easy to work with

Easy to cut

Score the smooth face with a sharp knife, snap the board over a straight edge and then cut through the glass fibre membrane from the opposite side. Alternatively, Glasroc F MULTIBOARD cuts easily with a fine-toothed hand or power saw.

Easy to fix

Glasroc F MULTIBOARD can be:

- Screwed 25mm into timber substrate
- Screw fixed to metal systems such as **GypWall CLASSIC** or **Gyplyner**
- Fixed directly to masonry using the **Drilyner** system

Butt the board edges lightly together. If screwing into place always use British Gypsum Drywall Screws. There's no need to pre-drill or countersunk, but fixings must be at least 10mm from the board edges.

Easy to joint

Smooth, continuous, crack-free lining surfaces ready for decoration can be created using standard Gyproc jointing materials and simple jointing techniques.

Easy to decorate

Glasroc F MULTIBOARD comes with a super smooth and durable surface that can be left undecorated in many situations. Alternatively it can be:

- Painted with standard emulsion finishes, without pre-preparation
- Wallpapered, ideally sizing the surface to make application and subsequent wet-stripping easier
- Skim finished using Thistle BoardFinish, Thistle MultiFinish or Thistle Magnetic Plaster.

Glasroc F MULTIBOARD

A versatile high performance board



Where do you turn when regular boards aren't up to the job? Glasroc F MULTIBOARD

Now you can forget using single purpose boards in those areas needing extra performance.

Glasroc F MULTIBOARD is specially designed using glass re-inforced gypsum to out-perform other boards across the five different areas where you'll need it most.

So you no longer have to worry about costly wastage, as any surplus at the end of a job simply goes back into the van, saving you time and money on your next project.

“Gyproc”, “Thistle”, “Gypframe” and “Glasroc” are all registered trademarks of Saint-Gobain Construction Products UK Limited. “Isover” is a registered trademark of Saint-Gobain Isover and “Artex” is a registered trademark of Saint-Gobain Construction Products UK Limited.

Saint-Gobain Construction Products UK Limited is a limited company registered in England under company number 734396, having its registered office at Saint-Gobain House, Binley Business Park, Coventry, CV3 2TT, UK. Saint-Gobain Construction Products UK Limited trades as British Gypsum for part of its business activities.

British Gypsum reserves the right to revise product specification without notice. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work. For a comprehensive and up-to-date library of information visit the British Gypsum website at: british-gypsum.com. For information about products supplied by Artex Limited or Saint-Gobain Isover please see their respective websites.

“British Gypsum” is a registered trademark of Saint-Gobain Construction Products UK Limited.



Technical enquiries

British Gypsum
Technical Advice Centre
East Leake
Loughborough
Leicestershire
LE12 6HX

Telephone: 0115 945 6123
Fax: 0115 945 1616
Email: bgtechnical.enquiries@bpb.com

British Gypsum October 2015 BG-GMB-DL-1501

british-gypsum.com

